

18-unit Subwoofer

SUB-18

INTRODUCTION

SUB-18 subwoofer, The cabinet is designed with a number of M8 hanging points, which can be installed in all directions and angles, supporting hoisting and bracket installation, and the trapezoidal cabinet design can be placed on the ground as a listening speaker, and the subwoofer has a round hole on it, which can be used as a full-range speaker with a round hole at the bottom of the base to form a PA system, redefining the new concept of flexible application and providing unprecedented practicality.



Flexible ways to use:



Stage feedback



Mobile use

SUB-18

SPECIFICATIONS

Model	SUB-18
type	Single 18 subwoofer
Frequency range (-10dB)	34Hz-300Hz
Axial sensitivity	96dB/1W/1m
impedance	8ohms
Maximum sound pressure level	Continuous: 126dB Peak: 132dB
Rated power	800W
Long-term maximum power	1600W
Peak power	3200W
Coverage angle	/
LF unit	18" driver × 14" voice coil
High frequency unit	/
Cabinet material	High-density boards, water-based coatings
Enter the connector	2× NL4 speaker socket
Hanging point	not
handle	Yes
color	black
Installation:	Ground placement
Gross/net weight	48.5kg/43.8kg
Dimensions (HxWxD)	698x560x595mm

SUB-18